

## ST213 Product Bulletin

### GENERAL INFORMATION

ST213 was formulated as an opaque white colored, slow to medium setting hot melt glue stick. Suggested uses include adhesion to rigid plastics, light metals and some plastics.

<b>Application Temperature</b>	340° - 375°F
<b>Viscosity at 350° F</b>	11,000 ± 2000 cps. @ 350°F
<b>Melt Point</b>	202° F ± 5° F
<b>Set Speed</b>	Medium Slow
<b>Product Form</b>	Hot Melt Glue Sticks
<b>Applicator</b>	GG100H, GG220, GG300 High Temperature Glue Guns
<b>Packaging</b>	25 lbs. per carton 1200 pounds per pallet
<b>Shelf Life</b>	3 plus years

Revised: January 1, 2010

Components contained in this product conform to USDA and FDA regulations for use in food packaging, as stated in the Federal Food and Drug and Cosmetic Act, Title 21 under section 175 - 105. This guarantee is also intended to comply with USDA's "Policy Governing Inspection of Packaging Materials".

**Note:** The data presented is based upon tests believed to be reliable; however, Western American, Inc., does not guarantee their accuracy or completeness. Western American, Inc., assumes no responsibility for results obtained or for incidental or consequential damages arising from the use of this data.