

ST213

SECTION VI - REACTIVITY DATA

STABILITY - STABLE

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS - CARBON MONOXIDE

CONDITIONS TO AVOID - TEMPERATURES OVER 400F MAY CAUSE RESIN
DEGRADATION

HAZARDOUS POLYMERIZATION - CANNOT OCCUR

SECTION VII - SPILL OR LEAK PROCEDURES

SPILL - SWEEP UP MATERIAL TO PREVENT SLIPPING, ALLOW MOLTEN SPILLS TO COOL
BEFORE SCRAPING UP AND DISPOSING.

WASTE DISPOSAL METHOD - IN ACCORDANCE WITH LOCAL
REGULATIONS

SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED

VENTILATION - YES, PROVIDE ADEQUATE VENTILATION, DO NOT USE IN CONFINED
SPACES

PROTECTIVE GLOVES - YES

EYE PROTECTION - YES

SECTION IX - PRECAUTIONS OR OTHER COMMENTS

STORAGE AND HANDLING - STORE IN COOL DRY PLACE, OPTIMUM
TEMPERATURE 70 F.

PICK UP MATERIAL IMMEDIATELY TO ELIMINATE SLIPPING HAZARDS.