



## ST39

---

### SECTION VI - REACTIVITY DATA

---

STABILITY - STABLE

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS - CARBON MONOXIDE

CONDITIONS TO AVOID - TEMPERATURES OVER 400F MAY CAUSE RESIN  
DEGRADATION

HAZARDOUS POLYMERIZATION - CANNOT OCCUR

---

### SECTION VII - SPILL OR LEAK PROCEDURES

---

SPILL - SWEEP UP MATERIAL TO PREVENT SLIPPING, ALLOW MOLTEN SPILLS TO COOL  
BEFORE SCRAPING UP AND DISPOSING.

WASTE DISPOSAL METHOD - IN ACCORDANCE WITH LOCAL  
REGULATIONS

---

### SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED

---

VENTILATION - YES, PROVIDE ADEQUATE VENTILATION, DO NOT USE IN CONFINED  
SPACES

PROTECTIVE GLOVES - YES

EYE PROTECTION - YES

---

### SECTION IX - PRECAUTIONS OR OTHER COMMENTS

---

STORAGE AND HANDLING - STORE IN COOL DRY PLACE, OPTIMUM  
TEMPERATURE 70 F.

PICK UP MATERIAL IMMEDIATELY TO ELIMINATE SLIPPING HAZARDS.